



HIGH PERFORMANCE HIGHLIGHT FOR EXTERIOR COMMERCIAL APPLICATIONS

FAST-SEAL[®] HIGH PERFORMANCE FABRIC DOOR

HIGH SPEED

Fast-Seal opens at up to 50 inches per second for improved traffic flow, productivity and energy savings for heavy-duty applications and day in, day out operation.

TAKES-A-HIT FUNCTIONALITY

Patented Break-Away™ bottom bar resets in seconds without tools; dual cut-off switches automatically shut off motor upon impact.

COUNTERBALANCE & TENSION SYSTEM

Withstands high wind loads and negative pressure environments. Features lifetime warranty on all counterweights and main tensioning components.

STATE-OF-THE-ART WIRELESS

Ry-Wi[®] Wireless System technology eliminates coil cords. Features two-way communication with total frequency control for added safety.

5-YEAR WARRANTY

Fast-Seal is backed by a 5-year limited warranty on motor and 3-ply Rylon[®] panel material; 2-year limited warranty on mechanical/electrical components.

MAXIMUM SAFETY

Pathwatch[®] Safety Light System, dual photo eyes in side columns plus bottom bar reversing edge - all standard safety features.

DURABLE PANEL MATERIAL

Puncture-resistant, vertically-flexible/laterally-stiff 3-ply Rylon[®] panel helps panel remain in guides even under wind or pressure.

CONTROL & PERFORMANCE

Watertight, NEMA 4X System 4[®] door controller plus heavy duty gear box/motor for precise control of door positioning, speed adjustment and more. Independent tension system maintains constant panel tension.



Discover why leading plant managers, engineers and contractors specify Rytec High Performance Doors.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change. © 2023 Rytec Corporation LIT051523

RytecDoors.com 888-GO-RYTEC

info@rytecddoors.com P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403, Jackson, WI 53037-0403

QUALITY. PERFORMANCE. RELIABILITY.