

HIGH PERFORMANCE HIGHLIGHT FOR FLEXIBLE EDGE APPLICATIONS

FLEXTEC® SOFT-EDGE HIGH PERFORMANCE DOOR

FLEXIBLE BY DESIGN

Engineered to flex around obstructions and easily release from side columns if needed yet durable against wind and pressure resistance, the FlexTec® eliminates entrapment concerns.

Self-Repairing Capabilities

Automatically self-repairs without user intervention if impacted from either direction reducing downtime, maintenance and repairs.

MAXIMUM SPEED

Operates up to 4 times faster than competitive doors. The FlexTec door opens at up to 100 inches per second reducing risk of impact.

MAXIMUM **S**AFETY

High-tech Advanced³ Light Curtain Safety System, Pathwatch® Safety Light System and flexible bottom edge - all standard safety features.

INDUSTRY-LEADING WARRANTY

FlexTec is backed by a 1 million cycle/5-year* warranty on motor/mechanical components, drive teeth and 1-ply Rylon® panel material; 2-year limited warranty on electrical components.

Accommodates Larger Openings


Now FlexTec models provides flexibility to even larger openings, up to 16' wide (-XL) and up to 20' high (-T), with the same great soft bottom edge.

DURABLE MATERIALS

Low-friction drive system, edge-to-edge seals, removable/replaceable 20" windows and 1-ply Rylon[®] panel for sustained reliability.

CONTROL & PERFORMANCE

Watertight, NEMA 4X System 4® Controller plus heavy duty gear box/motor for unmatched reliability in the most demanding high cycle environments.



Discover why leading plant managers, engineers and contractors specify Rytec High Performance Doors.

American Owned, American Made







◆ Watch All Rytec Testimonials

*Whichever occurs first. Specifications subject to change. © 2023 Rytec Corporation LIT051523

RytecDoors.com 888-GO-RYTEC

info@rytecdoors.com P: 262.677.9046 F: 262.677.2058 One Cedar Parkway, PO Box 403, Jackson, WI 53037-0403