

DIMENSIONAL VARIABLES DRAWING NOT TO SCALE; DIMENSIONS IN INCHES				
DOOR NO.	A	B	C	H
MILLIMETERS				
ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS AND ROUNDED UP TO THE NEAREST 10MM				
ELECTRICAL OPTIONS				
☐ 460v - 3ph ☐ 230v/208v - 3ph ☐ 230v - 1ph ☐ 480v OPEN DELTA, UNGROUND (\$)		☐ 575v - 3ph (\$) (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)		
STANDARD FEATURES				
1. CARBON STEEL POWDER COATED HEAD & SIDE COLUMN COMPONENTS. 2. SMARTSURROUND ADVANCED DETECTION AND ALERT SYSTEM. 3. VARIABLE DOOR OPENING SPEED; UP TO 60"/SEC. 4. PROGRAMMABLE UPPER AND LOWER LIMITS. 5. SYSTEM 4+ DRIVE AND CONTROL. 6. BRAKE RELEASE LEVER ON SIDE COLUMN. 7. ELECTRICAL FAIL SAFE REVERSING EDGE. 8. HEAVY DUTY ROLLERS AND GUIDE TRACK 9. INSULATED PANEL SLATS 10. DOOR APPROVED FOR USE IN AND OUTSIDE HVHZ 11. DOOR APPROVED FOR LARGE MISSILE IMPACT 12. REGISTERED BY FBC APPROVAL # FL28502-R3 13. REGISTERED BY MIAMI DADE NOA # 23-0929.05 14. CONCRETE ANCHORS TO BE 1/2" DIA. X 4-1/2" LONG, RED HEAD ITW TRUBOLT WEDGE OR HILTI KWIK BOLT 4 EXPANSION ANCHORS. SHALL BE INSTALLED FOLLOWING ALL RECOMMENDATIONS AND SPECS OF THE ANCHOR MANUFACTURER. ANCHORS TO BE INSTALLED IN MIN. 4000PSI CONCRETE WITH MIN. EMBEDMENT OF 2-1/4".				
UPGRADE OPTIONS				
BRAKE RELEASE LEVER: ☒ SIDE COLUMN (\$) ☐ REMOTE MOUNT (\$) ☐ BOTH (\$)				
☐ SLANT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)				
☐ FLAT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)				
☐ FRONT AND BOTTOM HEAD COVERS ONLY (\$)				
☐ RIGHT HAND DRIVE				
☐ ROTARY DISCONNECT (\$)				
☐ BT44 (BLUETOOTH ACCESS TERMINAL) (\$)				
SIDE COLUMN MOUNT: ☐ LH ☐ RH ☐ NONE-REMOTE				
☐ BT44 NIGHT SWITCH (\$)				
FUNCTION: _____				
ACTIVATION OPTIONS (\$)				
☐ — PUSHBUTTON		☐ DUAL LOOP CONTROLLER		
☐ — PULL CORDS		☐ RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT)		
☐ — MOTION DETECTOR		— 1 BTN TRANSMITTER		
☐ — PRESENCE DET.		— 2 BTN TRANSMITTER		
☐ — MOTION/PRESENCE		— 4 BTN TRANSMITTER		
OPTION NOTES				
(\$) = PRICING CHANGE IF NOT INCLUDED IN QUOTE				
PLEASE SPECIFY VOLTAGE				
RYTEC CORPORATION ONE CEDAR PARKWAY, JACKSON, WI 53037-0403				
APPROVAL DRAWING SPIRAL HZ (ROUNDHEAD) FOR DOOR WIDTH UP TO 16'-0", HEIGHT UP TO 20'-11"				
CUSTOMER: _____				
LOCATION: _____				
DATE: _____				REV.: B
DRAWING NO.: 726-01T				