

DIMENSIONAL VARIABLES

DRAWING NOT TO SCALE; DIMENSIONS IN INCHES

DOOR NO.	A	B	C	F	M	K	H
MILLIMETERS							

ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS
REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS
AND ROUNDED UP TO THE NEAREST 10MM

ELECTRICAL OPTIONS

- | | |
|---|--|
| ☐ 460v - 3ph | ☐ 575v - 3ph (\$) |
| ☐ 230v/208v - 3ph | (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER) |
| ☐ 230v - 1ph | |
| ☐ 480v OPEN DELTA, UNGROUNDED (\$) | |

STANDARD FEATURES

- SIDE COLUMN AND HEAD CONSOLE POWDER COATED RYTEC SILVER.
- INTELLIGENT LIGHT CURTAIN SYSTEM IN DOOR LINE TO 6'-0" ABOVE FINISHED FLOOR.
- SMARTSURROUND ADVANCED DETECTION AND ALERT SYSTEM.
- VARIABLE DOOR OPENING SPEED; UP TO 24"/SEC.
- PROGRAMMABLE UPPER AND LOWER LIMITS.
- SYSTEM 4+ DRIVE AND CONTROL.
- BRAKE RELEASE LEVER ON SIDE COLUMN.

UPGRADE OPTIONS

- ☐ RIGHT HAND DRIVE
- ☐ ROTARY DISCONNECT (\$)
- ☐ BTA4 (BLUETOOTH ACCESS TERMINAL) (\$)
- NIGHT SWITCH FUNCTION: _____
- ☐ SELECTOR SWITCH ON CONTROL BOX (\$)
- FUNCTION: _____
- ☐ FULL HEIGHT ACTIVE REVERSING EDGE SENSOR (\$)

PANEL OPTIONS

- ☒ INSULATED SOLID SLATS (\$)
- WINDOWS (\$)
- ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ OTHER _____
- VENTS (\$)
- ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ OTHER _____
- VISION HEIGHT (DIM 'J')
- ☐ 33" ☐ 39" ☐ 51"
- UP TO FOUR (4) VISION/VENT SLATS PER GROUP WITH AT LEAST ONE (1) SOLID SLAT SEPARATING GROUPS.
- OR UP TO SEVEN (7) VISION/VENT SLATS PER GROUP W/ AT LEAST TWO (2) SOLID SLATS SEPARATING GROUPS.

ACTIVATION OPTIONS (\$)

- | | |
|--|--|
| ☐ PUSHBUTTON | ☐ DUAL LOOP CONTROLLER |
| ☐ PULL CORDS | ☐ RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT) |
| ☐ MOTION DETECTOR | _____ 1 BTN TRANSMITTER |
| ☐ PRESENCE DET. | _____ 2 BTN TRANSMITTER |
| ☐ MOTION/PRESENCE | _____ 4 BTN TRANSMITTER |

OPTION NOTES

(\$) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

PLEASE SPECIFY VOLTAGE & SWITCH FUNCTION

RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING

SPIRAL LP MODEL SSN-LP-L

FOR DOOR WIDTH UP TO 13'-1", HEIGHT UP TO 12'-0"






CUSTOMER: _____

LOCATION: _____

DATE: _____

DRAWING NO.: 730-01T

REV.: A



FORMULAS

$$F = (B + 30.50); \text{ FOR } B < 91$$

$$F = (B + 11.00); \text{ FOR } B \geq 91$$

$$M = (B + 20.00); \text{ FOR } B < 91$$

$$M = B; \text{ FOR } B \geq 91$$

$$K = \text{NOT REQ'D}; \text{ FOR } B < 99$$

$$K = 72.00; \text{ FOR } B \geq 99$$

FINAL APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

REV	DESCRIPTION	DATE	BY