



*IF DOOR IS MOUNTED ON A FREEZER TO COOLER OPENING, DOOR, CONTROL PANEL, AND BLOWERS MUST BE MOUNTED TO THE WARM SIDE OF THE OPENING.

DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H

APPLICATION

COOLER TO COOLER COOLER TO FREEZER

ELECTRICAL OPTIONS

460v - 3ph 575v - 3ph (\$) (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)
 230v/208v - 3ph

STANDARD FEATURES

1. INSULATED 1" THICK BLUE FOAM PANEL & FIBERGLASS THERMAL BREAKS AROUND DOOR PERIMETER
2. QUAD SEALING SIDE COLUMNS, DUAL HEAD SEALS
3. 1/0 EXPANSION BOARD
4. 208, 230, & 460v REQUIRES 20 AMP SERVICE. 575V REQUIRES 15 AMP SERVICE

UPGRADE OPTIONS

- RIGHT HAND MOTOR MOUNT (LH STANDARD)
 - SINGLE SOURCE TRANSFORMER (\$)
 - PATHWATCH SAFETY SYSTEM (2) SETS (\$) (FIELD INSTALLED IF B<84")
 - ROTARY DISCONNECT (NON-FUSED) (\$)
 - SELECTOR SWITCH ON CONTROL BOX (\$) FUNCTION: _____
 - ACTIVE BOTTOM BAR (\$)
 - SAFETY PHOTOEYES (\$)
 - SIDE COLUMN WARMERS (\$) (120V/10A)*
 - UNHEATED E-ZONE BLOWER (\$) (120V/10A)*
- *BLOWER AND SIDE COLUMN WARMERS REQUIRE A 120V SERVICE -OR- A SINGLE SOURCE TRANSFORMER

OPTION NOTES

(\$) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

PLEASE SPECIFY VOLTAGE

RYTEC CORPORATION
 ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING
SURE-SEAL

FINAL APPROVAL SIGNATURE
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____
 PRINT NAME: _____
 SIGNATURE: _____
 DATE: _____

CUSTOMER: _____
 LOCATION: _____
 DATE: _____ REV.: _____
 DRAWING NO.: 2401-01T