



SIDE COLUMN PROFILE

DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	E	H

MODEL

MODEL: PREDAFLEX	
<u>PANEL MATERIAL</u>	<u>PANEL COLOR</u>
<input checked="" type="checkbox"/> VINYL	<input type="checkbox"/> BLUE
	<input type="checkbox"/> ORANGE

ELECTRICAL OPTIONS

- 460v - 3ph
- 230v/208v - 3ph
- 230v/208v - 1ph
- 575v - 3ph
- OTHER

STANDARD FEATURES

1. SEMI-AUTOMATIC SELF REPAIRING BOTTOM BAR
2. CLEAR VISION WINDOW, FULL WIDTH
3. (2) SAFETY PHOTOEYES (FIELD INSTALLED)
4. SYSTEM 4 AC DRIVE
5. PATHWATCH SAFETY SYSTEM

STANDARD OPTIONS

- SLANT HOOD
- RIGHT HAND DRIVE (LH STD.)
- ROTARY DISCONNECT
- TEMP < 50° REQR LOW TEMP PVC
- OTHERS (DESCRIBE IN NOTES)

ACTIVATION

- PHOTOEYE
- PULL CORDS
- MOTION DETECTOR
- RADIO CONTROL
- PUSHBUTTON
- FLOOR LOOP CONTROLLER
- OTHERS (DESCRIBE IN NOTES)

OPTION NOTES

NOTES:

RYTEC CORPORATION
ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING

PREDAD00R NXT® W/PREDAFLEX™ - SYSTEM
FOR DOOR WIDTH UP TO 14'-0", HEIGHT UP TO 14'-0"

CUSTOMER: _____

LOCATION: _____

DATE: _____ REV.: _____

DRAWING NO.: _____

APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

	X1	X2	X3	X4
WITHOUT HOOD	15.00	7.00	17.13	16.50
WITH HOOD	16.00	8.00	20.13	17.00

C = A + 12.50
E = A + X1 + X2
H = B + X3