



DOOR NO.	A	B	C	D	H

PANEL OPTIONS			
VINYL	2PLY (STD)	3PLY	USDA
<input type="checkbox"/> BLUE	<input type="checkbox"/> BLUE	<input type="checkbox"/> BLUE	<input type="checkbox"/> WHITE
<input type="checkbox"/> ORANGE	<input type="checkbox"/> ORANGE	<input type="checkbox"/> ORANGE	<input type="checkbox"/> BLUE
<input type="checkbox"/> WHITE	<input type="checkbox"/> GRAY	<input type="checkbox"/> GRAY	<input type="checkbox"/> MATTE
	<input type="checkbox"/> BROWN	<input type="checkbox"/> BROWN	<input type="checkbox"/> RED

ELECTRICAL OPTIONS	
<input type="checkbox"/> 460v - 3ph	<input type="checkbox"/> 575v - 3ph
<input type="checkbox"/> 230v/208v - 3ph	(INCLUDES NEMA 4
<input type="checkbox"/> 230v/208v - 1ph	METAL ENCLOSURE WITH
	575/460 TRANSFORMER)

- STANDARD FEATURES**
1. WIRELESS SEMI-AUTOMATIC SELF REPAIRING BOTTOM BAR WITH DUAL AIR SAFETY REVERSING EDGE.
 2. FRONT & REAR SAFETY PHOTOEYES.
 3. FIBERGLASS COMPOSITE SIDE COLUMNS WITH REMOVEABLE FRONT COVERS.
 4. STAINLESS BRACKETS & HARDWARE
 5. MOTOR CRANK & BRAKE LEVER ARE PROVIDED UNLESS COUNTERWEIGHT OPTION SELECTED. MOTOR COVER MUST BE REMOVED TO ACCESS.
 6. NEMA 4X CONTROL PANEL
 7. ONE (1) SET PATHWATCH SAFETY SYSTEM
 8. FULL WIDTH VISION PANEL.

- STANDARD OPTIONS**
- PLASTIC HOOD WITH MOTOR COVER
 - RIGHT HAND DRIVE (LH STANDARD)
 - COUNTERWEIGHTED MANUAL ASSIST
 - BRAKE RELEASE:
 - DOOR SIDE
 - THRU-WALL
 - BOTH
 - STAINLESS CLAD BOTTOM BAR
 - ROTARY DISCONNECT (NON-FUSED)
 - BRUSH SEALS (BLACK)
 - VINYL SEALS (WHITE)
 - IP65 SEVERE DUTY MOTOR
 - SELECTOR SWITCH ON CONTROL BOX
 - FUNCTION: _____
 - TEMP < 50° REQR LOW TEMP PVC
 - WINDRIB TYPE: ALUMINUM
 - WHITE FIBERGLASS
 - BLACK FIBERGLASS

- ACTIVATION**
- | | |
|--|---|
| <input type="checkbox"/> — PUSHBUTTON | <input type="checkbox"/> DUAL LOOP CONTROLLER |
| <input type="checkbox"/> — PULL CORDS | <input type="checkbox"/> RADIO CONTROL RCVR |
| <input type="checkbox"/> — TOUCHLESS PLATE | (INCLUDE MIN 2 XMIT) |
| <input type="checkbox"/> — MOTION DETECTOR | — 1 BTN TRANSMITTER |
| <input type="checkbox"/> — PRESENCE DET. | — 2 BTN TRANSMITTER |
| <input type="checkbox"/> — MOTION/PRESENCE | — 4 BTN TRANSMITTER |

OPTION NOTES

NOTES:
 PLEASE SPECIFY VOLTAGE AND PANEL COLOR

RYTEC CORPORATION
 ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING
PLEXLINE® - SYSTEM 4

APPROVAL SIGNATURE
 FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____
 PRINT NAME: _____
 SIGNATURE: _____
 DATE: _____

	X1	X2	X3	X4
WITHOUT HOOD	17.50	9.50	19.00	14.50
WITH HOOD	19.00	11.00	24.00	15.00

C = A + 14.00
 D = A + X1 + X2
 H = B + X3

* WINDOW LOCATION LOWERED IF TOP RIB EXCEEDS DOOR HEIGHT (B).
 * MAINTAIN 32 INCH SPACING BETWEEN ALL RIBS.

CUSTOMER: _____
 LOCATION: _____
 DATE: _____
 DRAWING NO.: 401164-00T REV.: —