



DIMENSIONAL VARIABLES				
DRAWING NOT TO SCALE; DIMENSIONS IN INCHES				
DOOR NO.	A	B	C	H
MILLIMETERS				
ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS AND ROUNDED UP TO THE NEAREST 10MM				
ELECTRICAL OPTIONS				
<input type="checkbox"/> 460v - 3ph		<input type="checkbox"/> 575v - 3ph		
<input type="checkbox"/> 230v/208v - 3ph		(INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)		
<input type="checkbox"/> 230v/208v - 1ph				
STANDARD FEATURES				
1. ONE THRU-BEAM PHOTOEYE SET MOUNTED IN SIDE COLUMN AT 16" FROM FLOOR-FACTORY INSTALLED.				
2. ONE THRU-BEAM PHOTOEYE SET-FIELD INSTALLED.				
3. VARIABLE DOOR OPENING SPEED; UP TO 60"/SEC				
4. DOOR CLOSING SPEED OF 30"/SECOND				
5. PROGRAMMABLE UPPER AND LOWER LIMITS				
6. SYSTEM 4 CONTROL BOX (8 1/2"x16 1/2")				
7. BRAKE RELEASE LEVER ON SIDE COLUMN				
8. ELECTRICAL FAIL SAFE REVERSING EDGE.				
9. ONE (1) SET PATHWATCH LEDS				
STANDARD OPTIONS				
BRAKE RELEASE LEVER				
<input checked="" type="checkbox"/> SIDE COLUMN <input type="checkbox"/> REMOTE MOUNT <input type="checkbox"/> BOTH				
<input type="checkbox"/> SLANT HOOD (INCLUDES FRONT/BOTTOM COVERS)				
<input type="checkbox"/> FLAT HOOD (INCLUDES FRONT/BOTTOM COVERS)				
<input type="checkbox"/> FRONT AND BOTTOM HEAD COVERS ONLY				
<input type="checkbox"/> RIGHT HAND DRIVE				
<input type="checkbox"/> ROTARY DISCONNECT				
<input type="checkbox"/> SELECTOR SWITCH ON CONTROL BOX				
FUNCTION: _____				
PANEL OPTIONS				
<input type="checkbox"/> INSULATED SOLID SLATS				
WINDOWS				
<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> OTHER _____				
VENTS				
<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> OTHER _____				
UP TO TWO (2) VISION/VENT SLATS PER GROUP WITH AT LEAST ONE (1) SOLID SLAT SEPARATING GROUPS.				
MAXIMUM TEN (10) VISION/VENT SLATS TOTAL IF A<=275				
MAXIMUM FOUR (4) VISION/VENT SLATS TOTAL IF A>275				
ACTIVATION				
<input type="checkbox"/> _____ PUSHBUTTON		<input type="checkbox"/> DUAL LOOP CONTROLLER		
<input type="checkbox"/> _____ PULL CORDS		<input type="checkbox"/> RADIO CONTROL RCVR		
<input type="checkbox"/> _____ MOTION DETECTOR		(INCLUDE MIN 2 XMIT)		
<input type="checkbox"/> _____ PRESENCE DET.		_____ 1 BTN TRANSMITTER		
<input type="checkbox"/> _____ MOTION/PRESENCE		_____ 2 BTN TRANSMITTER		
		_____ 4 BTN TRANSMITTER		
OPTION NOTES				
ADDITIONAL NOTES:				
PLEASE SPECIFY VOLTAGE				
RYTEC CORPORATION				
ONE CEDAR PARKWAY, JACKSON, WI 53037-0403				
APPROVAL SIGNATURE				
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED				
APPROVED BY: _____				
PRINT NAME: _____				
SIGNATURE: _____				
DATE: _____				
APPROVAL DRAWING				
SPIRAL MODEL SST-US/R				
FOR DOOR WIDTH UP TO 26'-3", HEIGHT UP TO 16'-4"				
CUSTOMER: _____				
LOCATION: _____				
DATE: _____				REV.: _____
DRAWING NO.: 401074-20T				

REV	DESCRIPTION	DATE	BY