



NOTES:
 RYTEC CORPORATION DOES NOT GUARANTEE A 100% FROST FREE DOOR. WITH THE HEATED BLOWER SYSTEM HOWEVER, THE AMOUNT OF FROST IS GREATLY REDUCED AND THE DEFROST RANGE EXPANDED TO APPROXIMATELY 16 FEET. DEPENDING ON SITE CONDITIONS AND RELATIVE HUMIDITY IT IS POSSIBLE FOR FROST TO FORM ON THE LOWER PORTION OF THE DOOR PANELS OR IN AREAS NOT COVERED BY THE AIR FLOW.

DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H
				23		

MODEL

MODEL: TS -	
PANEL MATERIAL	PANEL COLOR
<input type="checkbox"/> 2-PLY RILON	<input type="checkbox"/> BLUE
<input type="checkbox"/> 3-PLY RILON	<input type="checkbox"/> ORANGE
<input type="checkbox"/> OTHER	<input type="checkbox"/> OTHER

ELECTRICAL OPTIONS

- 460v - 3ph
- 230v/208v - 3ph
- 230v/208v - 1ph
- 575v - 3ph
- OTHER

STANDARD FEATURES

1. WIRELESS BOTTOM BAR (NO COIL CORD)
2. (1) FACTORY INSTALLED SIDE COLUMN PHOTOEYE
3. (1) FIELD INSTALLED PHOTOEYE
4. THRU BEAM PHOTOEYES IN LIEU OF STANDARD
5. FRONT MOUNTED HEATED BLOWER w/WALL BRACKETS
6. HEAT TAPE IN SIDE COLUMNS & ACROSS SPREADER
7. SYSTEM 4 AC DRIVE
8. LH MOTOR ASSEMBLY
9. 45 AMP SERVICE REQ IF A<72
- 60 AMP SERVICE REQ IF A>72
10. HOOD NOT RECOMMENDED
11. WINDOWS NOT RECOMMENDED

STANDARD OPTIONS

- SLANT HOOD FLAT HOOD
- 17" WINDOWS: ONE TWO THREE
- WINDRIBS: ONE TWO THREE
- THRU WALL BRAKE RELEASE
- 575/460V STEP DOWN TRANSFORMER INCLUDED IN RYTEC CONTROL BOX
- ROTARY DISCONNECT (NOT FUSED)
- OTHERS (DESCRIBE IN NOTES)

ACTIVATION

- PHOTOEYE
- PULL CORDS
- MOTION DETECTOR
- RADIO CONTROL
- PUSHBUTTON
- FLOOR LOOP
- OTHERS (DESCRIBE IN NOTES)

OPTION NOTES

NOTES:

RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING

TURBO SEAL® FREEZER w/ HEATED BLOWER- SYSTEM 4

APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

CUSTOMER: _____

LOCATION: _____

DATE: _____ REV.: _____

DRAWING NO.: 401054-02T