

RYTEC

HIGH PERFORMANCE DOORS

SPIRAL[®] VP

FOR TRANSITIONAL AREAS & HOSPITALITY SETTINGS



STYLISH AND SECURE



SPIRAL[®] VP

Modern Architectural Design, Quality Construction and Lasting Dependability

Featuring stylish design and genuine Spiral[®] components the Spiral VP door offers a new combination of quality, value and performance for lower speed, lower cycle applications. Now, hospitality and other commercial settings can enhance visual aesthetics without sacrificing performance or security. The Spiral VP integrates proven Spiral technology within a smaller footprint, allowing installations almost anywhere a conventional overhead door fits.

Sleek styling, quiet functioning and a compact profile make creating an appealing entryway or transition to an extended outdoor space now a reality.

Spiral VP performance is guaranteed with a **5-year limited warranty**.



Stylish Aesthetics

- Modern, crisp lines provide a stylish look ideal for new and renovated restaurant, hospitality and office settings

Assured Operation

- Unmatched 20-year warranty on high-cycle components including rollers, hinges and door tracks

Unparalleled Performance

- High performance operation for lower speed/cycle settings
- Day in, day out reliability

Solid Security

- Minimum 1 3/16-inch thick double-walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system

Proven Durability

- Constructed with heavy-duty, high quality components

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

RYTEC® SPIRAL® VP DIRECT DRIVE DOOR



Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

- Opens at 12 inches per second

Operation

- Quiet, low maintenance operation
- Direct drive motor connects directly to drive shaft
- No spring or cables
- Rated for 75 cycles per day
- Compact AC drive motor with variable speeds allows for soft acceleration and deceleration
- System 4® controller housed in a NEMA 4X rated enclosure



Construction

- 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



Powder coated side column cover



Rollers with sealed roller bearings

Warranty

- 20-year extended warranty on rollers, hinges and door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Door Panel Configuration

- Insulated door panel
- Vision slats
- Ventilated slats
- Integrated weatherseal

Lift Configuration

- Standard lift
- Vertical lift
- High lift

Safety

- Advanced³ Light Curtain Safety System

Options

- Chain hoist operator
- Powder coated finish available in RAL classic colors or custom match

RYTEC® SPIRAL® VP BALANCED DOOR



Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

- Opens at 8 inches per second

Operation

- Torsion spring balancing system assists the motor in opening
- Aircraft quality cable lift method
- Standard overhead door operator
- Rated for 50 cycles per day



Construction

- 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



Low-profile side track

Warranty

- 20-year extended warranty on rollers, hinges & door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Door Panel Configuration

- Insulated door panel
- Vision slats
- Ventilated slats
- Integrated weatherseal

Lift Configuration

- Standard lift
- Vertical lift
- High lift

Safety is Standard

- Thru-beam photo eye
- Note: Not intended for automatic closing applications**

Options

- Heavy duty operator
- Chain fall
- Powder coated finish available in RAL classic colors or custom match
- Extended life springs

Standard maximum sizes shown; larger sizes may be available upon request.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change
© 2020 Rytec Corporation LIT020520

RytecDoors.com
888-GO-RYTEC

info@rytecdoors.com
P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403
Jackson, WI 53037-0403

