



SPIRAL[®] LH[®]-HZ[®]

HIGH PERFORMANCE LOW HEADROOM HURRICANE ZONE DOOR



SPIRAL[®] LH[®]-HZ[®]

Low Headroom and High Security Join Forces Against Hurricane-Force Wind

The Spiral LH-HZ door (Low Headroom Hurricane Zone) brings high speed and high security to applications with limited headroom in high velocity hurricane zones. It has been certified to be in compliance with Miami-Dade County and the Florida Building Codes to withstand winds up to 175 mph. Notice of Acceptance (NOA) from Miami-Dade County, NOA No. 17-1106.02. Rigid aluminum slats with reinforced hinges combined with the galvanized steel side columns offer security and the strength to handle a hurricane.

Crisp lines give the Spiral LH-HZ door a stylish, high-tech look. The anodized aluminum slats will not corrode, so you can count on its look to last for many years even under the worst weather conditions.

Spiral LH-HZ high performance is guaranteed with a **5-year limited warranty**.



Withstands hurricane speed winds



Low headroom configuration

Low Headroom

- The low lintel design requires only 10 inches of headroom clearance

Extensive Testing

- Negative pressure, positive pressure and large and small missile impact testing conducted to ensure optimal performance in extreme weather conditions

Solid Security

- Minimum 1 3/16-inch thick double walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system

High Speed

- Opening speed of up to 60 inches per second improves traffic flow in fast-paced environments

Ultra Quiet

- High performance technology and low headroom angled track offer a quiet and unobtrusive operation

Energy Efficient & Tight Seal

- Aluminum slats and durable rubber membrane provides a 100% seal against dust, drafts and inclement weather

SPIRAL[®] LH[®]-HZ[®]

HIGH PERFORMANCE LOW HEADROOM HURRICANE ZONE DOOR



Size/Dimensions


- Maximum width up to 16'
- Maximum height up to 16'4"

Travel Speed

- Opening speed up to 60 inches per second

Unique Track Design

- Special track design allows door to fit in low headroom areas with as little as 10 inches of clearance above the door opening
- Compact, variable speed motor with soft acceleration and deceleration and braking for smooth starts and stops



Variable speed motor

Hurricane Tested

- Independently tested
- Certified to withstand missile impacts in high velocity wind zones
- Certified to withstand hurricane force winds of up to 175 mph



Heavy-duty panels built to withstand impact

Electrical Controls

- System 4[®] controller housed in a NEMA 4X rated enclosure with factory set parameters
- Intelligent processor monitors and controls power consumption during operation
- Advanced self-diagnostics for troubleshooting

System 4 shown with optional rotary disconnect



Standard maximum sizes shown; larger sizes may be available upon request.

Panel Design

- Integral rubber weatherseal between the slats provides a tight weatherseal across the entire panel
- Patented hinge design allows for removal and replacement of individual slats without disassembling the door panel



Integral rubber weatherseal

Safety is Standard

- Pathwatch[®] Safety Light System
- Dual thru-beam photo eyes
- Electric reversing edge
- Ry-Wi[®] Wireless System
- Mechanical brake release lever allows door opening in the event of power failure



Pathwatch warning lights and brake release lever shown

Certification

- Spiral HZ
Miami-Dade County, Florida NOA No. 17-1106.02, 11/8/2022
Florida Building Code: FL# 28502.1

Warranty

- Five-year limited warranty on motor/mechanical components and materials
- Two-year limited warranty on electrical components

Options

- Powder coated finish available in RAL classic colors or custom match
- Multiple door activation options available; contact factory for details



Powder coated slats shown

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change
© 2020 Rytec Corporation LIT020520

RytecDoors.com
888-GO-RYTEC

info@rytecdoors.com
P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403
Jackson, WI 53037-0403

