



DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H

**APPLICATION**

- COOLER TO COOLER     COOLER TO FREEZER

**ELECTRICAL OPTIONS**

- 460v - 3ph     575v - 3ph  
 230v/208v - 3ph    (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

**STANDARD FEATURES**

1. INSULATED 1" THICK BLUE FOAM PANEL & FIBERGLASS THERMAL BREAKS AROUND DOOR PERIMETER
2. QUAD SEALING SIDE COLUMNS, DUAL HEAD SEALS
3. WIRELESS (NO COIL CORD) THERMALLY ISOLATED COMPOSITE BOTTOM BAR WITH DUAL AIR REVERSING EDGE
4. SELF RESETTING BREAKAWAY BOTTOM BAR.
5. FRONT AND REAR SAFETY PHOTO EYES
6. (2) SETS PATHWATCH SAFETY SYSTEM
7. "RAD" TWO SPEED UNHEATED BLOWER SYSTEM
8. 208, 230, & 460v REQUIRES 20 AMP SERVICE. 575V REQUIRES 15 AMP SERVICE
9. BLOWERS AND SIDE COLUMN HEATERS REQUIRE SEPARATE 120V, 30 AMP SERVICE -OR- SINGLE SOURCE TRANSFORMER OPTION.

**STANDARD OPTIONS**

- RIGHT HAND MOTOR MOUNT (LH STANDARD)  
 SINGLE SOURCE TRANSFORMER  
 FLOOR MOUNTED SIDE COLUMN GUARD  
 ROTARY DISCONNECT (NON-FUSED)  
 SELECTOR SWITCH ON CONTROL BOX  
 FUNCTION: \_\_\_\_\_  
 BLOWER STYLE:  
 EZONE, SINGLE SPEED BLOWERS

**ACTIVATION**

- |  |   |
|--|---|
| <input type="checkbox"/> — PUSHBUTTON      | <input type="checkbox"/> DUAL LOOP CONTROLLER |
| <input type="checkbox"/> — PULL CORDS      | <input type="checkbox"/> RADIO CONTROL RCVR   |
| <input type="checkbox"/> — MOTION DETECTOR | (INCLUDE MIN 2 XMIT)                          |
| <input type="checkbox"/> — PRESENCE DET.   | — 1 BTN TRANSMITTER                           |
| <input type="checkbox"/> — MOTION/PRESENCE | — 2 BTN TRANSMITTER                           |
|  | — 4 BTN TRANSMITTER                           |

**OPTION NOTES**

NOTES:  
  
 \*\*\*PLEASE SPECIFY VOLTAGE\*\*\*

**RYTEC CORPORATION**

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING  
 TURBO-SEAL INSULATED GEN 2.0  
 WITH 2 SPEED BLOWER

CUSTOMER: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 DATE: \_\_\_\_\_ REV.: \_\_\_\_\_  
 DRAWING NO.: 2102-01T

**APPROVAL SIGNATURE**  
 FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED  
 APPROVED BY: \_\_\_\_\_  
 PRINT NAME: \_\_\_\_\_  
 SIGNATURE: \_\_\_\_\_  
 DATE: \_\_\_\_\_

\*IF DOOR IS MOUNTED ON A FREEZER TO COOLER OPENING, DOOR, CONTROL PANEL, AND BLOWERS MUST BE MOUNTED TO THE WARM SIDE OF THE OPENING.

		X1	X2
STANDARD	B <= 192.00	39.00	32.00
EXTRA TALL (XT)	B > 192.00	41.00	34.00