

Summary	Cleaning of the 2ply and 3ply				
Products Affected	All roll doors with Rilon panels				
Key Word Tags	Cleaning, 2Ply, 3Ply				
Tools/Equipment (If Required)	Soft, lint free cloth or soft sponge				
Parts/Materials (If Required)					
Related Media					
Author	Randy Meyer, RevA M. Burzlaff	Issue Date	3/12/2010	Status	Active

Please Read The Entire Bulletin Before Proceeding

Cleaning of the 2-ply and 3-ply Rilon panel material.

The following steps are recommended for cleaning Rilon panels at different stages. Choose the step that best meets your needs and contaminates.

Step 1) To remove accumulated contaminants from Rilon panels, a mild detergent (dish soap) solution mixed with water is recommended. To prevent scratches to the surface use a soft rag or sponge. Abrasive cleaners should be avoided.

Step 2) To remove mold and mildew, a Sodium Hypochlorite solution (chlorine bleach) 10-20% mix with water can be used. For best results apply the solution to the panel and let stand for up to five minutes, and then clean with soft rag or sponge.

Step 3) To remove organic residues, such as grease, oil, or soot, use denatured ethyl or isopropyl alcohol. Saturate a clean, soft rag and wipe the area. LIMIT THIS PROCESS WITH RESPECT TO FREQUENCY, AND THE AMOUNT OF ALCOHOL USED. Too much can cause the coating to become brittle.

Step 4) To remove inorganic residues such as metal contamination, mineral deposits, or masonry cement, use muriatic acid, Follow instructions on can and use small amounts followed by rinsing with water.

Step 5) For extremely dirty panels which did not come clean with any if the above methods you can try a ketone solvent, such as acetone or MEK (methyl ethyl ketone). You could also use PVC pipe cleaner, which is a mixture of the two solvents. USE A VERY SMALL AMOUNTS BY DAMPENING A SOFT RAG. FIRST TRY A SMALL AMOUNT IN A LESS OBVIOUS AREA TO SEE WHAT THE EFFECT IS.

The above mentioned cleaners and solvents can be purchased at local hardware or home improvement centers.

NOTE: AFTER CLEANING WITH ABOVE METHODS RINSE PANEL THOROUGHLY WITH CLEAN WATER.

Any questions please contact Rytec Customer Support at 1-800-628-1909