



Summary	Insulated Panel Storage				
Products Affected	Turbo Seal Insulated				
Key Word Tags	Panel, Storage, Insulated, Turbo seal				
Tools/Equipment (If Required)					
Parts/Materials (If Required)					
Related Media					
Author	J. Malinowski Rev A. M. Burzlaff	Issue Date	5-24-13	Status	Active

Please Read The Entire Bulletin Before Proceeding

Rytec's Insulated foam panel is composed of several layers of different material. Improper storage can result in damage to the panel and will void your warranty.

PANEL MUST BE INSTALLED 2 WEEKS AFTER DELIVERY. FAILURE TO DO SO WILL CAUSE CURLING OF THE PANEL AND WILL VOID THE WARRANTY.

If the panel is not being installed the same day as delivery, proper storage procedure must be followed!

Insulated Foam Panel Storage

- 1) Keep panel indoors
- 2) Keep panel dry
- 3) Keep out of direct sunlight
- 4) Keep cool (DO NOT exceed temperatures over 90° F)
- 5) Store panel in a VERTICAL position.
DO NOT STORE HORIZONTALLY-Laying the panel flat, or on a storage rack can damage the lamination of the panel after periods of time.

Should damage be found, please contact Rytec immediately. In most cases the damage can be quickly, easily, and permanently repaired if taken care of properly.



If you have any questions please contact Rytec Customer Support at 1-800-628-1909.