



## DIMENSIONAL VARIABLES

DRAWING NOT TO SCALE; DIMENSIONS IN INCHES

DOOR NO.	A	B	C	H
MILLIMETERS				

ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS  
REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS  
AND ROUNDED UP TO THE NEAREST 10MM

## ELECTRICAL OPTIONS

- ☐ 460v - 3ph  
☐ 230v/208v - 3ph  
☐ 230v - 1ph  
☐ 480v OPEN DELTA, UNGROUNDED (\$)
- ☐ 575v - 3ph (\$) (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

## STANDARD FEATURES

- ONE THRU-BEAM PHOTOEYE SET MOUNTED IN SIDE COLUMN AT 16" FROM FLOOR-FACTORY INSTALLED.
- ONE THRU-BEAM PHOTOEYE SET-FIELD INSTALLED.
- VARIABLE DOOR OPENING SPEED; UP TO 60"/SEC
- DOOR CLOSING SPEED OF 24"/SECOND
- PROGRAMMABLE UPPER AND LOWER LIMITS
- SYSTEM 4 CONTROL BOX (8 1/2"x16 1/2")
- BRAKE RELEASE LEVER ON SIDE COLUMN
- ELECTRICAL FAIL SAFE REVERSING EDGE.
- HEAVY DUTY ROLLERS AND GUIDE TRACK
- CARBON STEEL POWDER COATED HEAD & SIDE COLUMN COMPONENTS
- INSULATED PANEL SLATS
- DOOR APPROVED FOR USE IN AND OUTSIDE HVHZ
- DOOR APPROVED FOR LARGE MISSILE IMPACT
- REGISTERED BY FBC APPROVAL # FL28502-R3
- REGISTERED BY MIAMI DADE NOA # 23-0929.05

## STANDARD OPTIONS

- ☐ SLANT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)  
☐ FLAT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)  
☐ FRONT AND BOTTOM HEAD COVERS ONLY (\$)  
☐ RIGHT HAND DRIVE  
☐ REMOTE MOUNTED EGRESS LEVER (\$)  
☐ BT44 (BLUETOOTH ACCESS TERMINAL) (\$)  
 NIGHT SWITCH FUNCTION: \_\_\_\_\_

## ACTIVATION OPTIONS (\$)

- ☐ PRESENSE SENSOR  
☐ PULLCORDS  
☐ RADIO CONTROL w/2 X-MITTERS  
☐ MOTION DETECTOR  
☐ PUSHBUTTON  
☐ FLOOR LOOP CONTROLLER  
☐ OTHERS (DESCRIBE IN NOTES)

## OPTION NOTES

(\$ ) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

— PATHWATCH SAFETY SYSTEM

\*\*\*PLEASE SPECIFY VOLTAGE\*\*\*

## RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

## APPROVAL DRAWING

## SPIRAL-HZ ROUNDHEAD

FOR DOOR WIDTH UP TO 16'-0", HEIGHT UP TO 16'-4"

CUSTOMER: \_\_\_\_\_

LOCATION: \_\_\_\_\_

DATE: \_\_\_\_\_

DRAWING NO.: 401074-10T

REV.: 02

## FINAL APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE  
SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: \_\_\_\_\_

PRINT NAME: \_\_\_\_\_

SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

02	UPDATED FOR CURRENT APPROVALS	12/19/23	JMM
REV	DESCRIPTION	DATE	BY