

RYTEC

HIGH PERFORMANCE DOORS

PHARMA-SEAL® HIGH PERFORMANCE ROLL-UP DOOR

PHARMA-SEAL®

High-Speed Roll-Up Door Engineered for cGMP and "Class-Rated" Facilities

The Pharma-Seal® is engineered to comply with cGMP guidelines and is the tightest sealing, most reliable, high-performance roll-up door available. The simple design that is fully enclosed with stainless steel side columns and head assembly has no external parts.

Engineered for pharmaceutical high-cycle environments, the Pharma-Seal has a flush membrane switch and flush manual release handle making it easy to clean yet provide the reliability required for uninterrupted facility operations.



Easy Cleaning

- Fully enclosed 304 stainless steel side and hood covers
- Smooth panel for cleaning

Self-Sealing

- Minimal gap for curtain and hidden wind knobs for entire perimeter seal

Safety is Standard

- Advanced³ Light Curtain Safety System
- Counterbalanced manual release

Low Profile

- Requires only 9-inches of side frame clearance
- Requires only 14-inches of head clearance

Smooth Operation

- Advanced System 4® door controller enables precise door positioning, speed adjustment and control of all door functions

Manual Release

- Flush manual release handle to open door if power is lost

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

PHARMA-SEAL[®]

HIGH PERFORMANCE ROLL-UP DOOR



Size/Dimensions

- Up to 10'W x 10'H
- 14" headroom above lintel
- 12" head projection
- 8" side column projection
- 9" side clearances
- Motor placement on left side only

Travel Speed

- Opening speed up to 50 inches per second

Operation

- Variable-speed AC drive provides soft acceleration and deceleration
- Independent opening and closing speeds provide flexibility to meet any application

Engineered for Compliance

- Fully enclosed stainless steel hood seals the top of the door eliminating the need for a weather gasket that could eventually create particles in the air and on the floor
- Fully enclosed side frames, constructed of 304 stainless steel and #4 finish are easy to clean and remove
- Stainless clad bottom bar with only 3-inch profile height
- Fabric loop seal forms a tight seal on the floor



Flush membrane switch allows controls to be mounted remotely

Electrical Controls

- System 4[®] controller housed in a NEMA 4X rated enclosure with factory set parameters
- Intelligent processor monitors and controls power consumption during operation
- Advanced self-diagnostics for troubleshooting

System 4 shown with optional rotary disconnect



Panel Design

- 2-ply USDA/FDA-compliant multifilament panel
- Smooth surface for easy cleaning and wash-down
- Withstands industry standard 0.10" W.C. of room pressurization

Safety is Standard

- Advanced³ Light Curtain Safety System
- Counterbalanced manual release system incorporates fully-enclosed counterweight and brake release allowing door to open with the flip of a lever



Flush manual release

Warranty

- One-year limited warranty on mechanical and electrical components
- Three-year limited warranty on 2-ply USDA panel material



Options

- Blue and white (USDA/FDA-compliant) or red door panel color options
- 316 stainless steel for head and side frames
- Vulcanized vision windows or full width vision panel

Shown with optional windows



See Our Full Line of Clean Application Doors Online at [RytecDoors.com](https://www.RytecDoors.com)

- Plexline[®] Clean
- Pharma-Roll[®]
- Clean-Roll[®]

Download Our High Performance Door Clean & Compliant Brochure



Standard maximum sizes shown; larger sizes may be available upon request.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change
© 2023 Rytec Corporation LT051523

RytecDoors.com
888-GO-RYTEC

info@rytecdoors.com
P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403
Jackson, WI 53037-0403

RYTEC

HIGH PERFORMANCE DOORS