

SPIRAL® VP

Modern Architectural Design, Quality Construction and Lasting Dependability

Featuring stylish design and genuine Spiral® components the Spiral® VP rigid rolling door offers a new combination of quality, value and performance for lower speed, lower cycle applications. Now, hospitality and other commercial settings can enhance visual aesthetics without sacrificing performance or security. The Spiral VP integrates proven Spiral technology within a smaller footprint, allowing installations almost anywhere a conventional overhead door fits.

Sleek styling, quiet functioning and a compact profile make creating an appealing entryway or transition to an extended outdoor space now a reality.

Spiral VP performance is quaranteed with a **5-year limited warranty**.







Stylish Aesthetics

 Modern, crisp lines provide a stylish look ideal for new and renovated restaurant, hospitality and office settings

Assured Operation

 Unmatched 20-year warranty on highcycle components including rollers, hinges and door tracks

Unparalleled Performance

- High performance operation for lower speed/cycle settings
- · Day in, day out reliability

Solid Security

- Minimum 1 3/16-inch thick double walled aluminum slats
- Integral rubber weatherseal
- Continuous heavy-duty hinge system

Proven Durability

• Constructed with heavy-duty, high quality components

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

Vision slats

Ventilated slats

Lift Configuration

Door Panel Configuration

Insulated door panel

Integrated weatherseal

Vertical lift

Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

Opens at 12 inches per second

Operation

- · Quiet, low maintenance operation
- Direct drive motor connects directly to drive shaft
- No spring or cables
- · Rated for 75 cycles per day
- Compact AC drive motor with variable speeds allows for soft acceleration and deceleration
- System 4[®] controller housed in a NEMA 4X rated enclosure

Construction

- · 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



side column cover



Rollers with sealed roller bearings

High lift

Standard lift

Safety

Advanced³ Light Curtain Safety System

Warranty

- 20-year extended warranty on rollers, hinges and door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Options

- Chain hoist operator
- Powder coated finish available in RAL classic colors or custom match

Food and

Rytec® Spiral® VP Balanced Door

Size/Dimensions

- Up to 14'W x 14'H
- Multiple door configurations based on lift requirements

Travel Speed

· Opens at 8 inches per second

Operation

- Torsion spring balancing system assists the motor in opening
- Aircraft quality cable lift method
- Standard overhead door operator
- Rated for 50 cycles per day



Construction

- · 'Rytec silver' powder coated finish for increased durability
- Heavy-duty extruded aluminum door hinges
- Polyurethane rollers with sealed roller bearings
- No visible mounting hardware



Low-profile side track

Warranty

- 20-year extended warranty on rollers, hinges & door track
- Five-year limited warranty on motor/mechanical components
- Two-year limited warranty on electrical components

Door Panel Configuration

- Insulated door panel
- Vision slats

Automotive

- Ventilated slats
- Integrated weatherseal

Lift Configuration

- Standard lift
- Vertical lift

Ô

Security

High lift

Safety is Standard

Thru-beam photo eye

Note: Not intended for automatic closing applications

Options

- · Heavy duty operator
- · Chain fall
- · Powder coated finish available in RAL classic colors or custom match
- Extended life springs

Standard maximum sizes shown; larger sizes may be available upon request.











Watch All Rytec Testimonials

888-GO-RYTEC info@rytecdoors.com P: 262.677.9046 F: 262.677.2058 One Cedar Parkway, PO Box 403 Jackson, WI 53037-0403

