RYTEC. Quick Ship PREDADOOR® NXT® PROGRAM

The Quick Ship PredaDoor® NXT® Program provides faster order-to-ship turnaround of the top-selling Rytec PredaDoor NXT. Once the specifications noted below are met, the doors are processed for shipment within 15 days or less.

Door Model: Rytec PredaDoor®NXT®

Drive System: Direct-drive, variable-speed AC drive, left-hand or

right-hand mounted motor

Electrical: 460V, 230V/208V, & 575V all come in both 3PH and 1PH

Door Panel Material: Vinyl, 2-ply or 3-ply Rylon® **Door Panel Color:** Blue, brown, gray or orange

Wind Ribs: 2 aluminum (standard) or fiberglass (option);

additional wind ribs available

Size/Dimensions: Width and height up to 12 ft Vision: 30-in full-width vision panel

Controller: System 4® door controller; MS4 controller (option)

Safety Features: Pathwatch® Safety Light System, thru-beam photo eyes, pneumatic reversing edge, and Ry-Wi® Wireless System

Activation: Any standard activation

Warranty: 2-year limited warranty on mechanical and electrical;

3-year limited warranty on 2-ply panel material

Optional: Hood and motor covers

Takes a Hit[™] and Resets

- Break-Away[™] tabs allow the wireless bottom bar to releases in either direction without damage
- Exclusive NXT Quick-Set[™] repair system permits the operator to reset the door



Full Perimeter Seal

- Edge-to-edge brush seal at the top of the door and two brush seals in each side column
- Vinyl loop forms tight seal along floor



Total Digital Control

- Precise door positioning, infinite speed adjustments and total control of all door functions
- Compact BTA4 remote door controller available



*Note:15-Day period begins once a signed approval is received specifying door dimensions and clearances required for installation.

American Owned, American Made









◀ Watch All Rytec Testimonials

Specifications subject to change © 2023 Rytec Corporation LIT051623 RytecDoors.com 888-GO-RYTEC

85

info@rytecdoors.com P: 262.677.9046 F: 262.677.2058 One Cedar Parkway, PO Box 403 Jackson, WI 53037-0403

