



HIGH-PERFORMANCE HIGHLIGHT FOR EXTERIOR COMMERCIAL APPLICATIONS

FAST-SEAL[®] HIGH-PERFORMANCE FABRIC DOOR

HIGH SPEED

Fast-Seal opens at up to 50 inches per second for improved traffic flow, productivity and energy savings for heavy-duty applications and day in, day out operation.

TAKES-A-HIT FUNCTIONALITY

Patented Break-Away[™] bottom bar resets in seconds without tools; dual cut-off switches automatically shut off motor upon impact.

COUNTERBALANCE & TENSION SYSTEM

Withstands high wind loads and negative pressure environments. Features lifetime warranty on all counterweights and main tensioning components.

STATE-OF-THE-ART WIRELESS

Ry-Wi[®] Wireless System technology eliminates coil cords. Features two-way communication with total frequency control for added safety.

5-YEAR WARRANTY

Fast-Seal is backed by a 5-year limited warranty on motor and 3-ply Rylon[®] panel material; 2-year limited warranty on mechanical/electrical components.

MAXIMUM SAFETY

Pathwatch[®] Safety Light System, dual photo eyes in side columns plus bottom bar reversing edge - all standard safety features.

DURABLE PANEL MATERIAL

Puncture-resistant, vertically-flexible/laterally-stiff 3-ply Rylon[®] panel helps panel remain in guides even under wind or pressure.

CONTROL & PERFORMANCE

Watertight, NEMA 4X System 4[®] door controller plus heavy duty gear box/motor for precise control of door positioning, speed adjustment and more. Independent tension system maintains constant panel tension.



Discover why leading plant managers, engineers and contractors specify Rytec High-Performance Doors.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change. © 2024 Rytec, a Nucor company LIT091224

RytecDoors.com 888-GO-RYTEC

info@rytecdoors.com P: 262.677.9046

W223N16601 Cedar Parkway, Jackson, WI 53037-0403

QUALITY. PERFORMANCE. RELIABILITY.