



HIGH-PERFORMANCE HIGHLIGHT

FOR FULL VISIBILITY LOW HEADROOM APPLICATIONS

SPIRAL[®] LH[®]-FV[®] FULL VISION

LOW HEADROOM DESIGN

Special track design for installation in areas with as little as 11 inches of clearance.

FULL-WIDTH VISION SLATS

Continuous, undivided LEXAN[™] vision slats (up to 18' wide) for maximum visibility and fog-free performance.

MAXIMUM SPEED

Operates at much faster speeds than conventional doors. Spiral LH-FV doors open at rates up to 100 inches per second.

MAXIMUM LONGEVITY

Industrial-strength construction and materials ensure extreme durability for virtually uninterrupted operation. MARGARD[™] coated LEXAN is shatter-proof, break, scratch and UV-light resistant.

MARKET-LEADING WARRANTY

5-year mechanical, materials and components; 2-year electrical components; 7-year LEXAN vision slats.

MAXIMUM SAFETY

Standard safety features including SmartSurround[®] Advanced Detection & Alert System and Advanced³ Light Curtain Safety System.

CONTROL & PERFORMANCE

Watertight, NEMA 4X System 4[®] Controller plus heavy-duty gear box/motor for unparalleled reliability in the most demanding high cycle environments.

TRUSTED BY PROFESSIONALS

Thousands of Spiral[®] doors can be found in major commercial, auto and government applications throughout North America.



Discover why leading design architects, engineers and contractors specify Rytec High-Performance Doors.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change. © 2024 Rytec, a Nucor company LIT091224

RytecDoors.com 888-GO-RYTEC

info@rytecdoors.com P: 262.677.9046

W223N16601 Cedar Parkway, Jackson, WI 53037-0403

QUALITY. PERFORMANCE. RELIABILITY.