



HIGH PERFORMANCE HIGHLIGHT FOR FULL VISIBILITY LOW HEADROOM APPLICATIONS

SPIRAL[®] LH[®]-FV[®] FULL VISION

LOW HEADROOM DESIGN

Special track design for installation in areas with as little as 10 inches of clearance.

FULL-WIDTH VISION SLATS

Continuous, undivided LEXAN[™] vision slats (up to 18' wide) for maximum visibility and fog-free performance.

MAXIMUM SPEED

Operates at much faster speeds than conventional doors. Spiral LH-FV doors open at rates up to 100 inches per second.

MAXIMUM LONGEVITY

Industrial-strength construction and materials ensure extreme durability for virtually uninterrupted operation. MARGARD[™] coated LEXAN is shatter-proof, break, scratch and UV-light resistant.

MARKET-LEADING WARRANTY

5-year mechanical, materials and components; 2-year electrical components; 7-year LEXAN vision slats.

MAXIMUM SAFETY

Standard safety features including SmartSurround[™] Advanced Detection & Alert System and Advanced³ Light Curtain Safety System.

CONTROL & PERFORMANCE

Watertight, NEMA 4X System 4[®] Controller plus heavy-duty gear box/motor for unparalleled reliability in the most demanding high cycle environments.

TRUSTED BY PROFESSIONALS

Thousands of Spiral[®] doors can be found in major commercial, auto and government applications throughout North America.



Discover why leading design architects, engineers and contractors specify Rytec High Performance Doors.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change. © 2022 Rytec Corporation LIT031522

RytecDoors.com 888-GO-RYTEC

info@rytecdoors.com P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403, Jackson, WI 53037-0403

QUALITY. PERFORMANCE. RELIABILITY.