



**DIMENSIONAL VARIABLES**

DRAWING NOT TO SCALE; DIMENSIONS IN INCHES

DOOR NO.	A	B	C	H

MILLIMETERS

ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS  
REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS  
AND ROUNDED UP TO THE NEAREST 10MM

**ELECTRICAL OPTIONS**

- 460v - 3ph
- 230v/208v - 3ph
- 230v - 1ph
- 480v OPEN DELTA, UNGROUNDED (\$)
- 575v - 3ph (\$)  
(INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

**STANDARD FEATURES**

1. SIDE COLUMN AND HEAD CONSOLE POWDER COATED RYTEC SILVER.
2. INTELLIGENT LIGHT CURTAIN SYSTEM IN DOOR LINE TO 6'-0" ABOVE FINISHED FLOOR.
3. SMARTSURROUND ADVANCED DETECTION AND ALERT SYSTEM.
4. VARIABLE DOOR OPENING SPEED; UP TO 100"/SEC.
5. PROGRAMMABLE UPPER AND LOWER LIMITS.
6. NEMA 4X SYSTEM 4 CONTROL BOX (8.5"x16.5").
7. BRAKE RELEASE LEVER ON SIDE COLUMN.

**UPGRADE OPTIONS**

- BRAKE RELEASE LEVER**
- SIDE COLUMN
  - REMOTE MOUNT (\$)
  - BOTH (\$)
  - SLANT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)
  - FLAT HOOD (INCLUDES FRONT/BOTTOM COVERS) (\$)
  - FRONT AND BOTTOM HEAD COVERS (\$)
  - RIGHT HAND DRIVE
  - ROTARY DISCONNECT (\$)
  - BTA4 (BLUETOOTH ACCESS TERMINAL) (\$)
  - SIDE COLUMN MOUNT:  LH  RH  NONE-REMOTE
  - BTA4 NIGHT SWITCH (\$)
  - FUNCTION: \_\_\_\_\_
  - SELECTOR SWITCH ON CONTROL BOX (\$)
  - FUNCTION: \_\_\_\_\_
  - FULLY VENTILATED SLATS (\$)
  - FULL HEIGHT ACTIVE REVERSING EDGE SENSOR (\$)

**ACTIVATION OPTIONS (\$)**

- PUSHBUTTON
- PULL CORDS
- MOTION DETECTOR
- PRESENCE DET.
- MOTION/PRESENCE
- DUAL LOOP CONTROLLER
- RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT)
- \_\_\_ 1 BTN TRANSMITTER
- \_\_\_ 2 BTN TRANSMITTER
- \_\_\_ 4 BTN TRANSMITTER

**OPTION NOTES**

(\$ ) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

\*\*\*PLEASE SPECIFY VOLTAGE\*\*\*

**RYTEC CORPORATION**

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

**APPROVAL DRAWING**

**SPIRAL FV MODEL STT-S**

FOR DOOR WIDTH UP TO 20', HEIGHT UP TO 19'-8"

CUSTOMER: \_\_\_\_\_

LOCATION: \_\_\_\_\_

DATE: \_\_\_\_\_ REV.: \_\_\_\_\_

DRAWING NO.: 729-01T

**FINAL APPROVAL SIGNATURE**

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: \_\_\_\_\_

PRINT NAME: \_\_\_\_\_

SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

REV	DESCRIPTION	DATE	BY