



**DIMENSIONAL VARIABLES**

DRAWING NOT TO SCALE; DIMENSIONS IN INCHES

DOOR NO.	A	B	C	F	M	K	H
MILLIMETERS							

ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS  
REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS  
AND ROUNDED UP TO THE NEAREST 10MM

**ELECTRICAL OPTIONS**

- 460v - 3ph
- 230v/208v - 3ph
- 230v - 1ph
- 480v OPEN DELTA, UNGROUNDED (\$)
- 575v - 3ph (\$)  
(INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

**STANDARD FEATURES**

- SIDE COLUMN AND HEAD CONSOLE POWDER COATED RYTEC SILVER.
- INTELLIGENT LIGHT CURTAIN SYSTEM IN DOOR LINE TO 6"-0" ABOVE FINISHED FLOOR.
- SMARTSURROUND ADVANCED DETECTION AND ALERT SYSTEM.
- VARIABLE DOOR OPENING SPEED; UP TO 60"/SEC.
- PROGRAMMABLE UPPER AND LOWER LIMITS.
- NEMA 4X SYSTEM 4 CONTROL BOX (8.5"x16.5").
- BRAKE RELEASE LEVER ON SIDE COLUMN.

**UPGRADE OPTIONS**

- BRAKE RELEASE LEVER**
- SIDE COLUMN  REMOTE MOUNT (\$)  BOTH (\$)
  - RIGHT HAND DRIVE
  - ROTARY DISCONNECT (\$)
  - BTA4 (BLUETOOTH ACCESS TERMINAL) (\$)
  - SIDE COLUMN MOUNT:  LH  RH  NONE-REMOTE
  - BTA4 NIGHT SWITCH (\$)
- FUNCTION: \_\_\_\_\_
- SELECTOR SWITCH ON CONTROL BOX (\$)
  - FUNCTION: \_\_\_\_\_
  - FULL HEIGHT ACTIVE REVERSING EDGE SENSOR (\$)

**PANEL OPTIONS**

- INSULATED SOLID SLATS (\$)
  - WINDOWS (\$)
    - 1  2  3  4  OTHER \_\_\_\_\_
  - VENTS (\$)
    - 1  2  3  4  OTHER \_\_\_\_\_
  - VISION HEIGHT (DIM 'J')
    - 33"  39"  51"
- UP TO FOUR (4) VISION/VENT SLATS PER GROUP WITH AT LEAST ONE (1) SOLID SLAT SEPARATING GROUPS.  
OR UP TO SEVEN (7) VISION/VENT SLATS PER GROUP W/ AT LEAST TWO (2) SOLID SLATS SEPARATING GROUPS.

**ACTIVATION OPTIONS (\$)**

- PUSHBUTTON
- PULL CORDS
- MOTION DETECTOR
- PRESENCE DET.
- MOTION/PRESENCE
- DUAL LOOP CONTROLLER
- RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT)
- \_\_\_\_\_ 1 BTN TRANSMITTER
- \_\_\_\_\_ 2 BTN TRANSMITTER
- \_\_\_\_\_ 4 BTN TRANSMITTER

**OPTION NOTES**

(\$ ) = PRICING CHANGE IF NOT INCLUDED IN QUOTE  
\*\*\*PLEASE SPECIFY VOLTAGE\*\*\*

**FORMULAS**

F = (B + 30.50); FOR B < 91  
F = (B + 11.00); FOR B >= 91

M = (B + 20.00); FOR B < 91  
M = B; FOR B >= 91

K = NOT REQ'D; FOR B < 99  
K = 72.00; FOR B >= 99

**FINAL APPROVAL SIGNATURE**

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: \_\_\_\_\_

PRINT NAME: \_\_\_\_\_

SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_

**RYTEC CORPORATION**  
ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING  
SPIRAL LH MODEL SSN-L

FOR DOOR WIDTH UP TO 13'-1", HEIGHT UP TO 13'-1"

CUSTOMER: \_\_\_\_\_

LOCATION: \_\_\_\_\_

DATE: \_\_\_\_\_

DRAWING NO.: 725-01T

REV.: A

REV	DESCRIPTION	DATE	BY