



DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H
-	-	-	-	23	-	-

PANEL OPTION		
2PLY (STD)	3PLY (\$)	USDA (\$)
<input type="checkbox"/> BLUE	<input type="checkbox"/> BLUE	<input type="checkbox"/> WHITE
<input type="checkbox"/> ORANGE	<input type="checkbox"/> ORANGE	<input type="checkbox"/> BLUE
<input type="checkbox"/> GRAY	<input type="checkbox"/> GRAY	<input type="checkbox"/> MATTE
<input type="checkbox"/> BROWN	<input type="checkbox"/> BROWN	<input type="checkbox"/> RED

ELECTRICAL OPTIONS	
<input type="checkbox"/> 460v - 3ph	<input type="checkbox"/> 575v - 3ph (\$)
<input type="checkbox"/> 480v OPEN DELTA, UNGROUNDED (\$)	(INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

- STANDARD FEATURES**
1. WIRELESS BOTTOM BAR (NO COIL CORD)
 2. (1) FACTORY INSTALLED SIDE COLUMN PHOTOEYE
 3. (1) FIELD INSTALLED PHOTOEYE
 4. FRONT MOUNTED HEATED BLOWER w/WALL BRACKETS
 5. HEAT TAPE IN SIDE COLUMNS & ACROSS SPREADER (TWO (2) SEPARATE 120V, 20AMP POWER SUPPLYS OR SINGLE SOURCE TRANSFORMER REQUIRED)
 6. LH MOTOR ASSEMBLY ONLY
 7. STEEL NEMA 4 CONTROL PANEL ENCLOSURE WITH FUSED ROTARY DISCONNECT.
 8. 45 AMP SERVICE REQ IF A<72
60 AMP SERVICE REQ IF A>72
 9. HOOD NOT AVAILABLE

- UPGRADE OPTIONS (\$)**
- 17" LOW TEMP WINDOW (\$): ONE TWO THREE (WINDOWS ARE NOT RECOMMENDED IN FREEZERS)
- SINGLE SOURCE TRANSFORMER (\$)
- MOTOR HEATER (\$)
- CONTROL PANEL HEATER (\$)
- BTA4 (BLUETOOTH ACCESS TERMINAL) (\$)
NIGHT SWITCH FUNCTION: _____
- SELECTOR SWITCH ON CONTROL BOX (\$)
FUNCTION: _____

ACTIVATION OPTIONS (\$)	
<input type="checkbox"/> PUSHBUTTON	<input type="checkbox"/> DUAL LOOP CONTROLLER
<input type="checkbox"/> PULL CORDS	<input type="checkbox"/> RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT)
<input type="checkbox"/> MOTION DETECTOR	— 1 BTN TRANSMITTER
<input type="checkbox"/> PRESENCE DET.	— 2 BTN TRANSMITTER
<input type="checkbox"/> MOTION/PRESENCE	— 4 BTN TRANSMITTER

OPTION NOTES

(\$) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

PLEASE SPECIFY PANEL COLOR AND VOLTAGE

RYTEC CORPORATION
ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING
TURBO SEAL® FREEZER w/ HEATED BLOWER- SYSTEM 4

CUSTOMER: _____

LOCATION: _____

DATE: _____ REV.: _____

DRAWING NO.: 401054-02T

NOTES:
RYTEC CORPORATION DOES NOT GUARANTEE A 100% FROST FREE DOOR. WITH THE HEATED BLOWER SYSTEM HOWEVER, THE AMOUNT OF FROST IS GREATLY REDUCED AND THE DEFROST RANGE EXPANDED TO APPROXIMATELY 16 FEET. DEPENDING ON SITE CONDITIONS AND RELATIVE HUMIDITY IT IS POSSIBLE FOR FROST TO FORM ON THE LOWER PORTION OF THE DOOR PANELS OR IN AREAS NOT COVERED BY THE AIR FLOW. DOOR, CONTROL PANEL, AND DEFROST SYSTEM MUST BE MOUNTED TO THE WARM SIDE OF THE OPENING.

FINAL APPROVAL SIGNATURE
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____

PRINT NAME: _____

SIGNATURE: _____

DATE: _____