



NOTES:
 RYTEC CORP. DOES NOT GUARANTEE A FROST FREE DOOR. THE RANGE OF THE TEC LIGHTS IS APPROXIMATELY TEN (10) VERTICAL FEET. DEPENDING ON SITE CONDITIONS AND RELATIVE HUMIDITY, IT IS POSSIBLE FOR FROST TO BUILD UP ON THE LOWER PORTION OF THE DOOR PANEL. DOOR, DEFROST, AND CONTROL PANEL MUST BE MOUNTED TO THE WARM SIDE OF THE OPENING.

DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H
-	-	-	-	23	-	-

MODEL		
2PLY <input type="checkbox"/> BLUE <input type="checkbox"/> ORANGE <input type="checkbox"/> GRAY <input type="checkbox"/> BROWN	3PLY (\$) <input type="checkbox"/> BLUE <input type="checkbox"/> ORANGE <input type="checkbox"/> GRAY <input type="checkbox"/> BROWN	USDA (\$) <input type="checkbox"/> WHITE <input type="checkbox"/> BLUE MATTE <input type="checkbox"/> RED

ELECTRICAL OPTIONS	
<input type="checkbox"/> 460v - 3ph <input type="checkbox"/> 480v OPEN DELTA, UNGROUNDED (\$)	<input type="checkbox"/> 575v - 3ph (\$) (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)

STANDARD FEATURES
1. WIRELESS BOTTOM BAR (NO COIL CORD) 2. (1) FACTORY INSTALLED SIDE COLUMN PHOTOEYE 3. (1) FIELD INSTALLED PHOTOEYE 4. FRONT BLOWER AND HEAT LAMPS MOUNTED INDEPENDENTLY ON WALL 5. STEEL NEMA 4 CONTROL PANEL ENCLOSURE WITH FUSED ROTARY DISCONNECT FOR TEC LIGHTS 6. SYSTEM 4 AC DRIVE 7. LH MOTOR ASSEMBLY 8. 460V & 575V REQUIRE 30 AMP SERVICE 9. HOOD NOT RECOMMENDED 10. (1) SET PATHWATCH SAFETY SYSTEM

UPGRADE OPTIONS
17" LOW TEMP WINDOW (\$): <input type="checkbox"/> ONE <input type="checkbox"/> TWO <input type="checkbox"/> THREE (WINDOWS ARE NOT RECOMMENDED IN FREEZERS) <input type="checkbox"/> SINGLE SOURCE TRANSFORMER (\$) <input type="checkbox"/> MOTOR HEATER (\$) <input type="checkbox"/> CONTROL PANEL HEATER (\$) <input type="checkbox"/> BTA4 (BLUETOOTH ACCESS TERMINAL) (\$) NIGHT SWITCH FUNCTION: _____ <input type="checkbox"/> SELECTOR SWITCH ON CONTROL BOX (\$) FUNCTION: _____

ACTIVATION OPTIONS (\$)	
<input type="checkbox"/> PUSHBUTTON	<input type="checkbox"/> DUAL LOOP CONTROLLER
<input type="checkbox"/> PULL CORDS	<input type="checkbox"/> RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT)
<input type="checkbox"/> MOTION DETECTOR	<input type="checkbox"/> PRESENCE DET. — 1 BTN TRANSMITTER
<input type="checkbox"/> PRESENCE DET.	<input type="checkbox"/> MOTION/PRESENCE — 2 BTN TRANSMITTER
<input type="checkbox"/> MOTION/PRESENCE	<input type="checkbox"/> — 4 BTN TRANSMITTER

OPTION NOTES
 (\$) = PRICING CHANGE IF NOT INCLUDED IN QUOTE
 PLEASE SPECIFY PANEL COLOR AND VOLTAGE

RYTEC CORPORATION
 ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING
 TURBO SEAL® FREEZER BLOWER & TEC LIGHTS - SYS 4

CUSTOMER: _____
 LOCATION: _____
 DATE: 11/30/11
 DRAWING NO.: 401054-01T REV.: —

FINAL APPROVAL SIGNATURE
 FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: _____
 PRINT NAME: _____
 SIGNATURE: _____
 DATE: _____