



		X1	X2
STANDARD	B ≤ 192.00	39.00	32.00
EXTRA TALL (XT)	B > 192.00	41.00	34.00

\*IF DOOR IS MOUNTED ON A FREEZER TO COOLER OPENING, DOOR, CONTROL PANEL, AND BLOWERS MUST BE MOUNTED TO THE WARM SIDE OF THE OPENING.

DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H
----------	---	---	---	---	---	---

**APPLICATION**

- COOLER TO COOLER     COOLER TO FREEZER

**ELECTRICAL OPTIONS**

- 460v - 3ph     575v - 3ph (\$) (INCLUDES NEMA 4 METAL ENCLOSURE WITH 575/460 TRANSFORMER)  
 230v/208v - 3ph  
 480v OPEN DELTA, UNGROUNDED (\$)

**STANDARD FEATURES**

- INSULATED 1" THICK BLUE FOAM PANEL & FIBERGLASS THERMAL BREAKS AROUND DOOR PERIMETER
- QUAD SEALING SIDE COLUMNS, DUAL HEAD SEALS
- WIRELESS (NO COIL CORD) THERMALLY ISOLATED COMPOSITE BOTTOM BAR WITH DUAL AIR REVERSING EDGE
- SELF RESETTING BREAKAWAY BOTTOM BAR.
- FRONT AND REAR SAFETY PHOTO EYES
- (2) SETS PATHWATCH SAFETY SYSTEM
- "RAD" TWO SPEED UNHEATED BLOWER SYSTEM
- 208, 230, & 460v REQUIRES 20 AMP SERVICE. 575V REQUIRES 15 AMP SERVICE
- BLOWERS AND SIDE COLUMN HEATERS REQUIRE SEPARATE 120V, 30 AMP SERVICE -OR- SINGLE SOURCE TRANSFORMER OPTION.

**UPGRADE OPTIONS**

- RIGHT HAND MOTOR MOUNT (LH STANDARD)  
 SINGLE SOURCE TRANSFORMER (\$)  
 FLOOR MOUNTED SIDE COLUMN GUARD (\$)  
 ROTARY DISCONNECT (NON-FUSED) (\$)  
 BTA4 (BLUETOOTH ACCESS TERMINAL) (\$)  
 NIGHT SWITCH FUNCTION: \_\_\_\_\_  
 SELECTOR SWITCH ON CONTROL BOX (\$)  
 FUNCTION: \_\_\_\_\_  
 BLOWER STYLE:  
 EZONE, SINGLE SPEED BLOWERS (\$)

**ACTIVATION OPTIONS (\$)**

- |  |  |
|--|--|
| <input type="checkbox"/> — PUSHBUTTON      | <input type="checkbox"/> DUAL LOOP CONTROLLER                    |
| <input type="checkbox"/> — PULL CORDS      | <input type="checkbox"/> RADIO CONTROL RCVR (INCLUDE MIN 2 XMIT) |
| <input type="checkbox"/> — MOTION DETECTOR | — 1 BTN TRANSMITTER  |
| <input type="checkbox"/> — PRESENCE DET.   | — 2 BTN TRANSMITTER  |
| <input type="checkbox"/> — MOTION/PRESENCE | — 4 BTN TRANSMITTER  |

**OPTION NOTES**

(\$ ) = PRICING CHANGE IF NOT INCLUDED IN QUOTE

\*\*\*PLEASE SPECIFY VOLTAGE\*\*\*

**RYTEC CORPORATION**

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING  
 TURBO-SEAL INSULATED GEN 2.0  
 WITH 2 SPEED BLOWER

CUSTOMER: \_\_\_\_\_

LOCATION: \_\_\_\_\_

DATE: \_\_\_\_\_ REV.: \_\_\_\_\_

DRAWING NO.: 2102-01T

**FINAL APPROVAL SIGNATURE**

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY: \_\_\_\_\_

PRINT NAME: \_\_\_\_\_

SIGNATURE: \_\_\_\_\_

DATE: \_\_\_\_\_